

DATE OF DEPOSIT: January 3, 2001 Express Mail Number: EL 438566975US

I, Tammy S. McCarthy, hereby certify that this paper (along with any paper referred to as being attached or enclosed or actually enclosed) is being deposited with the United States Postal Service "EXPRESS MAIL POST OFFICE TO ADDRESSEE" service under 37 C.F.R. 1.10 on the date indicated above, with sufficient postage, and is addressed as follows:

ASSISTANT COMMISSIONER FOR PATENTS

BOX: PATENT APPLICATION

WASHINGTON, D.C. 20231.

Signature:

Date:

January 3, 2001

UNITED STATES PATENT APPLICATION

ON

GAS STREAM VORTEX MIXING SYSTEM AND METHOD

BY

Barry L. Phillips

BASI.IP2023 JRBJ

- 1 -

**TECHNICAL FIELD OF THE INVENTION**

This invention relates in general to the field of gas mixing and more particularly, but not by way of limitation, to a gas stream vortex mixing system and method for mixing power plant combustion exhaust gas.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 270

- 2 -

### BACKGROUND OF THE INVENTION

The electric utility industry strives to efficiently provide electric power while minimizing the impact that electrical generation has on the environment. One specific point of concern is reducing harmful exhaust gas emissions from power plants.

Power plants produce dangerous combustion gases, such as NO<sub>x</sub> (oxides of nitrogen like NO and NO<sub>2</sub>), which are exhausted as a by-product of electric generation. The combustion or flue gases are carried by large ducts or flues through treatment systems intended to reduce the NO<sub>x</sub> emissions. One commonly employed treatment process, called selective catalytic reduction (SRC), reduces NO<sub>x</sub> emissions by injecting an ammonia mixture into the combustion gases and passing the combined constituent gas, combustion gas mixed with the ammonia mixture, over a catalyst. The catalyst reacts with the harmful gas changing it into harmless gas comprised of nitrogen related compounds, thus reducing or eliminating the NO<sub>x</sub> emissions.

When the combustion gases are uniformly mixed with the ammonia mixture and passed over the catalyst within a specific temperature range, the catalyst is highly effective at reducing NO<sub>x</sub> emissions. However, a uniform constituent gas mixture is difficult to achieve given the volume of combustion gas which must be uniformly mixed within the large ducts. These ducts range in shape, such as rectangular and oval, and size, but often have passageways of 20 feet by 40 feet or more.

Frequently, the constituent gas flowing within the ducts develops small channels containing high concentrations of the various flue gas constituents (CO,

- 3 -

CO<sub>2</sub>, NO<sub>x</sub>, for example) and the injected ammonia, or rope flows, while the constituent gas throughout the remaining duct cross section will contain low concentrations of NO<sub>x</sub> making proper mixing with ammonia prior to the SCR most difficult. When such inhomogeneous constituent gas is passed through the catalyst, the rope flow zones exit the catalyst with high levels of flue gas constituents and/or ammonia that were not reacted by the catalyst due to the improper mixing of flue gas and ammonia. The remaining combustion gas with low concentrations of NO<sub>x</sub> will be catalyzed by the SCR, but the ammonia will be under utilized and emitted into the atmosphere at greater than acceptable concentration.

The remedy has generally been to inject more ammonia mixture into the combustion gas in the ducts to reduce the NO<sub>x</sub> emissions. While this does lower NO<sub>x</sub>, increasing the ammonia concentration is costly, inefficient, and results in increased ammonia emissions.

Another approach has been to place obstacles into the ducts to disrupt the flow of combustion gas in order to achieve an improved mixture of constituent gases. However, such obstacles create only turbulent flow of the combustion gases and provide only minimum improvement of the mixture of constituent gases. Additionally, the turbulence inducers generate resistance in the ducts which reduces the efficiency of the flow of combustion gases through the ducts and increases the load on the fan systems that move the combustion gases through the ducts.

Thus, a need exists for an improved system and method for mixing the stream of combustion gases and injected ammonia mixture into a uniform mixture of

ATTORNEY DOCKET NO.  
BASI.IP2023

PATENT APPLICATION

- 4 -

constituent gases. It is to such a gas stream mixing  
system and method that the present invention is directed.

- 5 -

SUMMARY OF THE INVENTION

The present invention provides a gas stream vortex mixing system for mixing gas. The gas stream vortex mixing system includes a duct provided with an outer surface defining an interior passageway operable for communicating a gas. The gas stream vortex mixing system further includes at least one nozzle and at least one wing. The wing is disposed within the interior passageway of the duct and is operable for generating at least one vortex. The nozzle is disposed within the interior passageway of the duct. The nozzle is operable to discharge a mixture into the interior passageway of the duct.

In another embodiment, a gas stream vortex mixing system for mixing combustion gas exhaust is provided. The gas stream vortex mixing system includes a duct provided with an outer surface defining an interior passageway operable for communicating a combustion gas. The gas stream vortex mixing system further includes at least one wing disposed within the interior passageway. The wing is operable for generating a vortex. The gas stream vortex mixing system also includes at least one nozzle disposed adjacent at least one wing within the interior passageway of the duct. The nozzle is operable to discharge a mixture into the vortex generated by the wing.

In yet another embodiment, the present invention provides for a method of mixing gas by creating a predictable and ordered vorticity. The method includes providing a gas stream vortex mixing system. The gas stream vortex mixing system includes a duct provided with

- 6 -

an outer surface defining an interior passageway operable for communicating a gas.

The gas stream vortex mixing system further includes at least one nozzle and at least one wing. The wing is disposed within the interior passageway of the duct and is operable for generating at least one vortex. The nozzle is disposed within the interior passageway of the duct. The nozzle is operable to discharge a mixture into the interior passageway of the duct.

The method includes providing a supply of combustion gas into the interior passageway of the duct such that the combustion gas passes about at least one of the wings of the gas stream vortex mixing system generating a vortex. The method further includes discharging the mixture from at least one nozzle into the vortex such that the mixture is homogenized with the combustion gas within the vortex.

In another embodiment, the present invention provides a method of mixing gas by creating a predictable and ordered vorticity. The method includes providing a gas stream vortex mixing system having a duct provided with an outer surface defining an interior passageway operable for communicating a combustion gas. The gas stream vortex mixing system is further provided with at least one wing having an asymmetrical airfoil shape with a defined camber line such that the wing is operable to more efficiently generate lift, resulting in stronger vorticity at lower gas flow resistance.

In yet another embodiment, the present invention provides for a more simple way to achieve most of the positive effects by shaping the wing from a flat plate

- 7 -

and forming the desired camber line into the plate along the span of the wing.

The wing is positioned within the interior passageway of the duct such that the chord line of the airfoil is substantially parallel to a line defining the direction of the flow of combustion gas within the interior passageway of the duct. The wing is operable for generating at least one vortex at one or more points on the wing. The gas stream vortex mixing system further includes at least one nozzle disposed adjacent the wing within the interior passageway of the duct. The nozzle is operable to discharge a mixture into the vortex generated by the wing.

The method includes providing a supply of combustion gas into the interior passageway of the duct such that the combustion gas passes near at least one of the wings of the gas stream vortex mixing system thereby generating a vortex. The method further includes discharging the mixture from at least one nozzle into the vortex such that the mixture is homogenized with the combustion gas within the vortex.

Other technical advantages are readily apparent to one skilled in the art from the following figures, description, and claims.



- 8 -

**BRIEF DESCRIPTION OF THE DRAWINGS**

For a more complete understanding of the present invention and the advantages thereof, reference is now made to the following brief description, taken in connection with the accompanying drawings and detailed description, wherein like reference numerals represent like parts, in which:

**FIGURE 1** is a side elevational view of a gas stream vortex mixing system according to an embodiment of the invention employing catalyst modules ;

**FIGURE 2** is a graph detailing a lift to drag ratio at an angle of attack of a given airfoil;

**FIGURE 3** is a side view of a symmetrical wing according to an embodiment of the present invention;

**FIGURE 4** is a side view of a cambered wing according to an embodiment of the present invention;

**FIGURE 5** is a side view of another embodiment of a wing constructed according to the present invention;

**FIGURE 6** is a perspective representation of a wing according to an embodiment of the present invention;

**FIGURE 7** is a top plan view of another embodiment of gas stream vortex mixing system of the present invention;

**FIGURE 8** is a top plan view of yet another embodiment of the gas stream vortex mixing system of the present invention;

**FIGURE 9** is a top plan view of another embodiment of the gas stream vortex mixing system of the present invention showing another arrangement of the wings;

- 9 -

**FIGURE 10** is side elevational view another embodiment of the gas stream vortex mixing system of the present invention;

**FIGURE 11** is a side elevational view of yet another embodiment of the gas stream vortex mixing system of the present invention.

- 10 -

**DETAILED DESCRIPTION OF THE INVENTION**

It should be understood at the outset that although an exemplary implementation of the present invention is illustrated below, the present invention may be implemented using any number of techniques, whether currently known or in existence. The present invention should in no way be limited to the exemplary implementations, drawings, and techniques illustrated below, including the exemplary design and implementation illustrated and described herein.

**FIGURE 1** is a side elevational view of a gas stream vortex mixing system 10 constructed in accordance with the present invention. The gas stream vortex mixing system 10 includes a duct 12, also commonly referred to as a flue, which is in communication with the combustion chamber of an electric power plant (not shown).

The duct 12 may be constructed from a variety of materials, such as sheet metal, is sized to receive a combustion gas 14 from the power plant combustion chamber (not shown). The manufacture and use of ducts 12 to communicate and direct the flow of combustion gases 14 is well known in the art therefore no further discussion is deemed necessary to teach one of ordinary skill in the art in the use of ducts 12.

The combustion gas 14 includes the exhaust gases produced as a by-product of the electric generation process. The duct 12 receives the combustion gas 14 into one end 16 thereof the duct 12. The duct 12 is provided with an outer surface 18 and an inner surface 20, the outer surface 18 and inner surface 20 defining an interior passageway 22 operable for communicating the combustion gas 14.

- 11 -

The gas stream vortex mixing system 10 further includes at least one wing 24. Although the wings 24 are substantially similar in construction and design, the wings 24 have been denoted alphanumerically for purposes of clarity wings 24a and 24b. The wings 24a and 24b will be discussed in greater detail hereinafter. The wings 24a and 24b are disposed within the interior passageway 22 of the duct 12.

The wings 24a and 24b may be constructed from a variety of materials, such as, but not limited to sheet metal or rigid polymeric materials, for example. The wings 24a and 24b may be attached to the inner surface 20 of the duct 12 in various ways including, but not limited to using a standard nut and bolt assembly, welding, or by other means which will readily suggest themselves to one of ordinary skill in the art.

The wings 24a and 24b are substantially configured having the attributes of airfoils and are operable for generating at least one vortex 26. The vortices 26a and 26b have been denoted alphanumerically for purposes of clarity. It is readily apparent that as the combustion gas 14 is communicated through the interior passageway 22 of the duct 12 and caused to pass about the wings 24a and 24b, the vortices 26a and 26b will be shed from the wings 24a and 24b respectively. The characteristics of the vortices 26a and 26b shed from wings 24a and 24b will be discussed in greater detail hereinafter.

The gas stream vortex mixing system 10 also includes at least one nozzle 40. The nozzles 40 are constructed substantially similar and have been denoted alphanumerically 40a and 40b for purposes of clarity. The nozzles 40a and 40b are connected to a supply line

- 12 -

42a and 42b, respectively, of a desired mixture, such as, but not limited to, ammonia or other chemical compounds beneficially injected into the combustion gas 14.

The nozzles 40a and 40b are disposed within the interior passageway 22 of the duct 12, and operable to inject, for example, an ammonia mixture 50, or other mixture of a desired chemical compound, into the combustion gas 14 carried in interior passageway 22 of the duct 12. One advantage of the gas stream vortex mixing system 10 of the present invention, is the delivery of the ammonia mixture 50a and 50b into an intense vortex 26a and 26b to create a well mixed constituent gas 60 comprising combustion gas 14 and the ammonia mixture 50.

It will be appreciated that the wings 24a and 24b are designed having certain airfoil characteristics to shed vortices 26a and 26b having desired attributes, such as the direction of circulation, velocity, intensity, and expansion. In this manner, the vortex 26a may be caused to collide with vortex 26b for the purpose of further generating a homogenous mixture of constituent gases. Additionally, the vortex 26a and 26b may be calculated so as to encompass and include the maximum amount of combustion gas 14 for mixing with the ammonia mixture 50 to eliminate rope flow containing high concentrations of the certain of the flue gas constituents, for example, CO, CO<sub>2</sub>, NO<sub>x</sub>.

Once the constituent gas 60 is well mixed by the vortices 26a and 26b with the ammonia mixture 50 it is passed over one or more catalyst modules 90. The catalyst modules 90 are operable to catalytically reduce the NO<sub>x</sub> in the constituent gas 60 by reacting with the

- 13 -

constituent gas 60 as it is passed over the catalyst modules 90. The reduced NOx emission gas 94 is then output from another end 92 of the duct 12. Thus, it can be appreciated that the gas stream vortex mixing system 10 of the present invention achieves the benefits of reduced emissions of NOx, more efficient use of the ammonia mixture 50, and longer life of the catalyst modules 90, due to the even distribution of constituent gas 60.

**FIGURE 2** is a graph 120 detailing a lift to drag ratio at an angle of attack of a given airfoil 122. It is appreciated that when designing an airfoil to implement for the gas stream vortex mixing system 10, consideration should be given to defining the desired characteristics of the airfoil to be employed. As such, the optimum design provides for an airfoil having a maximized lift to drag ratio with a minimized drag 124 at a given angle of attack. The lift of a given airfoil 122 is relative to the energy of the vortex shed by the airfoil 122. That is, the higher the lift the stronger the vortex. The graph 120 provides for the design of the airfoil 122 which will provide a maximum lift and minimum drag and prevent turbulent or disrupted flow associated with a stall condition about the airfoil 122.

As previously mentioned, a stall condition has the effect of generating turbulent flow which generates unpredictable and unstable air flow about an obstacle in the duct 12. However, the turbulent flow is not desirous in that it provides on limited mixing of the combustion gas 14 with the ammonia mixture 50 and substantially impairs the even flow of combustion gas 14 through the duct 12. This uneven flow creates an inefficient state

- 14 -

within the duct 12 which produces an increased load on fans which provide the combustion gas 14 to the duct 14 and drawing the constituent gas from the duct 12.

Thus, modeling provides opportunity to define an airfoil that generates a maximized lift to drag ratio while creating an optimized vortex. Furthermore, an airfoil 122 may produce a number of vortices along various point on the airfoil. Such an airfoil provides the gas stream vortex mixing system 10 with a predefined and ordered vorticity to generate a uniform and homogenous constituent gas 14. While the graph 120 is provided to illustrate modeling capabilities to derive suitable airfoils for the gas stream vortex mixing system 10, a variety of airfoils may be readily employed for such purposes.

**FIGURE 3** is a side view of a symmetrical wing 220 according to an embodiment of the present invention. It is appreciated that when designing wings, such as the wings 24a and 24b, shown in Fig. 1, to provide a given characteristic, a variety of wing configurations may be employed. The symmetrical wing 220 is an embodiment of one such configuration which is readily adapted to achieve the advantages and provide the benefits disclosed herein with reference to the wing 26 of the gas stream vortex mixing system 10. The symmetrical wing 220 has a chord line 222 defining a straight line extending the length of the cross section of the symmetrical wing 220.

**FIGURE 4** is a side view of a cambered wing 230 having a camber line 232 according to an embodiment of the present invention which may be readily employed for the purposes of generating a vortex, such as the vortices 26a and 26b shown in Fig. 1. The cambered wing 230 is

- 15 -

another embodiment of one such configuration which is readily adapted to achieve the advantages and provide the benefits disclosed herein with reference to the wing 26 of the gas stream vortex mixing system 10. The cambered wing 230, as with any wing or airfoil, has a chord line 234 defining a straight line extending the length of the cross section of the cambered wing 230.

**FIGURE 5** is a side view of another embodiment of a wing 240 constructed according to the present invention similarly having the camber line 232. The wing 240 is another embodiment of one such configuration which is readily adapted to achieve the advantages and provide the benefits disclosed herein with reference to the wing 26 of the gas stream vortex mixing system 10.

**FIGURE 6** is a perspective representation of a wing 250 according to an embodiment of the present invention. In this embodiment, the wing 250 constructed of a substantially rigid material, such as sheet metal. The wing 250 is angularly configured along a line 252 relative to the camber line 232 a wing, such as the wing 240 (see Fig. 10) or 230 (see Fig. 4), having the desired characteristics.

Because the wing 250 is substantially two-dimensionally constructed, the wing 250 will lack the complete characteristics of the wing, such as the wing 240 (see Fig. 10) or 230 (see Fig. 4). However, the wing 250 will achieve the general aerodynamic characteristics of the wing upon whose camber line 232 the wing 250 was modeled. In this embodiment, the wing 250 is a simple means for providing an optimized lift to drag ratio and a defined point (not shown) from which to shed the desired



- 16 -

vortex without constructing the full airfoils shown above.

While several airfoil and wing configurations have been shown it should be appreciated that other configurations (not shown) of airfoils and wings operable to achieve the advantages and obtain the benefits described herein will readily suggest themselves to one of ordinary skill in the art and are within the spirit and scope of the present invention as disclosed and claimed herein. An additional consideration to the design of the wing, such as the wing 24a and 24b (see Fig. 1), is interaction and effect of other wings 24 within the same duct 12.

Referring now to **FIGURE 7**, a top plan view of another embodiment of gas stream vortex mixing system 10 of the present invention is shown. In this embodiment, a plurality of wings 300 are denoted alphanumerically for purposes of clarity 300a, 300b, 300c, and 300d. The wings 300a and 300b are shown attached to one side 302 of the duct 12 while wing 300c and 300b are shown attached to an opposite side 304 of the duct 12.

In this manner, the vortices 320a, 320b, 320c and 320d generated by the wings 300a, 300b, 300c and 300d, respectively, create a predefined and ordered vorticity within the interior passageway 22 of the duct 12. The nozzles 322 are positioned near the point on the respective wing 300 where the vortex is shed. Such a configuration of the wings 300 and nozzles 322 is well adapted to provide a uniform and homogenous mixture of the constituent gases 60.

Referring to **FIGURE 8**, a top plan view of yet another embodiment of the gas stream vortex mixing system

- 17 -

10 of the present invention is shown. In this embodiment, a plurality of wings 350 are denoted alphanumerically for purposes of clarity 350a, 350b, 350c, and 350d. The wing 350a is shown attached to one side 302 of the duct 12 and the wing 350b is shown attached to an adjacent side 352 of the duct 12. The wing 350c is shown attached to the opposite side 304 of the duct 12 and wing 350d is shown attached to an adjacent side 354 of the duct 12.

It can be seen that vortices 360a, 360b, 360c and 360d rotate in a counter-clockwise direction due to the configuration of wings 350a, 350b, 350c and 350d, respectively. It may be beneficial to utilize wings 350 wherein the direction of rotation of the vortices, such as vortices 360a, 360b, 360c and 360d, is predetermined so as to further increase the uniformity of mixing of the combustion gases 14. In this manner, the vortices 360 can be caused to encompass the greatest possible amount of combustion gas 14 for optimum uniformity of constituent gas 60.

**FIGURE 9** shows a top plan view of another embodiment of the gas stream vortex mixing system 10 of the present invention. In this embodiment, a plurality of wings 380 are denoted alphanumerically for purposes of clarity 380a, 380b, 380c, 380d, 380e and 380f. The wings 380a and 380b are shown attached to one side 302 of the duct 12 while wing 380c and 380b are shown attached to an opposite side 304 of the duct 12. The addition of wings 380e and 380f to adjacent sides 352 and 354, respectively, of the duct 12 represent another configuration for optimizing the mixture of constituent gas 60. It is readily apparent that the plurality of

- 18 -

wings 380 are disposed substantially about the same plane within the interior passageway 22 of the duct 12. It is apparent that the vortices 382a and 382b rotate clockwise while vortices 382c, 382d, 382e, and 382f rotate counter-clockwise to provide uniform distribution and homogeneity of the constituent gas 60.

While several embodiments are shown with various placements of wings, such as wing 300, 350, and 380, it will be appreciated that any number or combination of wings 300, 350, and 380 having varying characteristics to generate vortices 320, 360, and 382 are possible to generate the uniform distribution of constituent gas 60 within the inner passageway 22 of the duct 12 and remain within the spirit and scope of the invention disclosed herein.

**FIGURE 10** shows another embodiment of the gas stream vortex mixing system 10 of the present invention employing a single wing 400 disposed within the center of the interior passageway 22 of the duct 12. In this embodiment, the wing 400 is suspended about the interior passageway 22. Such disposition of the wing 400 may be achieved, such as, but not limited to, attachment of the wing 400 to the supply line 42 providing the ammonia mixture 50.

In this manner, the wing 400 is operable to shed one vortex 402 from the tip of each wing 400. Additionally, whether the wing 400 is suspended within the interior passageway 22 of the duct 12 or attached to the inner surface 20 of the duct 12, it is readily apparent that the wing 400 is disposed such that the wing 400 generates lift and is disposed substantially parallel to direction 410 of the flow of combustion gas 14 through the duct 12.

- 19 -

It can be seen that the wing 400 is positioned such that the chord line (not shown) is substantially parallel to the direction 410 of the flow of combustion gas 14. More specifically, the chord line of the wing 400 may be positioned at an angle of attack of from 5 to 15 degrees, and optimally from 8 to 12 degrees, relative to the direction 410 of the flow of combustion gas 14. In this manner, the ordered flow for mixing combustion gas may be controlled to the maximum extent.

The nozzle 40 of the gas stream vortex mixing system 10 is shown disposed about a point on the wing 400 wherein the vortex 402 is shed. This placement of the nozzle 40 provides for optimum mixing of the ammonia mixture 50 with the combustion gas 14. Furthermore, while the nozzle 40 is shown injecting the ammonia mixture 40 in the direction 410 of the flow of combustion gas 14, it is appreciated that in another embodiment (not shown), the nozzle 40 may be reversed such that the ammonia mixture is injected in a direction opposite the direction 410 of the flow of combustion gas 14.

**FIGURE 11** is a side elevational view of yet another embodiment of the gas stream vortex mixing system 10 of the present invention. A plurality of wings 450, denoted 450a, 450b, 450c, and 450d, are attached to the inner surface 20 of the duct 12 along differing horizontal planes. The present embodiment describes yet another placement of wings within the interior passageway 22 to generate a predetermined and ordered vorticity to create a uniform mixture of constituent gas 60.

In the present embodiment, the nozzles 40 are placed substantially below the point on the wing where a vortex 452, denoted 452a, 452b, 452c, 452d, respectively, is

- 20 -

shed. In this manner the vortex 452 has had substantial time to develop in diameter to allow for uniform mixing of the ammonia mixture 50 with the combustion gas 14.

In another embodiment, a method of mixing gas by creating a predictable and ordered vorticity is provided. The method includes providing the gas stream vortex mixing system 10 including the duct 12. The duct 12 is provided with an outer surface 18 defining an interior passageway 22 operable for communicating a combustion gas. The gas stream vortex mixing system 10 includes at least one wing 450 disposed within the interior passageway of the duct 12. The wing 450 is operable for generating at least one vortex 452. The gas stream vortex mixing system 10 further includes at least one nozzle 40 disposed within the interior passageway 40 of the duct 12. The nozzle 40 is operable to discharge the ammonia mixture 50 into the interior passageway 50 of the duct 12.

The method includes providing a supply of combustion gas 14 into the interior passageway 14 of the duct 12 such that the combustion gas 14 passes about at least one of the wings 450. The method further includes discharging the ammonia mixture 50 from at least one nozzle 40 into the vortex 452 such that the ammonia mixture 50 is homogenized with the combustion gas 14 within the vortex 452.

Thus, it is apparent that there has been provided, in accordance with the present invention, a gas stream vortex mixing system 10 that satisfies one or more of the advantages set forth above. Although the preferred embodiment has been described in detail, it should be understood that various changes, substitutions, and

- 21 -

alterations can be made herein without departing from the scope of the present invention, even if all of the advantages identified above are not present. For example, the various embodiments shown in the drawings herein illustrate that the present invention may be implemented and embodied in a variety of different ways that still fall within the scope of the present invention.

Also, the techniques, designs, elements, and methods described and illustrated in the preferred embodiment as discrete or separate may be combined or integrated with other techniques, designs, elements, or methods without departing from the scope of the present invention. Other examples of changes, substitutions, and alterations are readily ascertainable by one skilled in the art and could be made without departing from the spirit and scope of the present invention.